

SAFETY DATA SHEET

Revision Date 21-Oct-2016

Version 1

1. IDENTIFICATION

Product identifier

Product Name 8691-SS BLACK

Other means of identification

Product Code DF-8691-SS

UN/ID no. UN1263

SKU(s) DF-8691-SS

Recommended use of the chemical and restrictions on use

Recommended Use No information available.

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

Vogel Automotive Coatings

1020 Albany Place SE

Orange City, IA 51041

Phone: 712-737-4993

Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Flammable liquids	Category 2

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

Highly flammable liquid and vapor



Appearance No information available

Physical state liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other Information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Tert-Butyl Acetate	540-88-5	10 - 30	*
Parachlorobenzotrifluoride	98-56-6	10 - 30	*
Butyl Acetate	123-86-4	5 - 10	*
Barium sulfate	7727-43-7	1 - 5	*
Methyl Amyl Ketone	110-43-0	1 - 5	*
Aromatic 150	64742-94-5	1 - 5	*
Aromatic 100	64742-95-6	1 - 5	*
Carbon Black	1333-86-4	1 - 5	*
Substituted benzotriazole	104810-48-2	0.1 - 1	*
Naphthalene	91-20-3	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures**General advice**

If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician immediately.
Ingestion	Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.
Self-protection of the first aider	Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Tert-Butyl Acetate 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m ³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m ³
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	-
Butyl Acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Barium sulfate 7727-43-7	TWA: 5 mg/m ³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Methyl Amyl Ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	No information available
Appearance	No information available	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	>= 98 °C / 208 °F	
Flash point	4 °C / 40 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.07	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	8.92 lbs/gal
Bulk density	No information available
Percent solids by weight	44.4%

Percent volatile by weight	17.9%
Percent solids by volume	34.0%
Actual VOC (lbs/gal)	1.6
Actual VOC (grams/liter)	191.3
EPA VOC (lbs/gal)	2.8
EPA VOC (grams/liter)	340.6
EPA VOC (lb/gal solids)	4.7

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tert-Butyl Acetate 540-88-5	= 4100 mg/kg (Rat)	> 2 g/kg (Rabbit)	> 2230 mg/m ³ (Rat) 4 h
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Butyl Acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12.6 mL/kg (Rabbit) = 12600 μ L/kg (Rabbit)	> 2000 ppm (Rat) 4 h
Aromatic 150 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Aromatic 100 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Substituted benzotriazole 104810-48-2	> 5000 mg/kg (Rat)	-	-
Naphthalene 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon Black 1333-86-4	A3	Group 2B	-	X
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic toxicity

Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands.

Target Organ Effects

Central nervous system, Eyes, Lymphatic System, Peripheral Nervous System (PNS), Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects

43.76% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Tert-Butyl Acetate 540-88-5	-	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	-
Parachlorobenzotrifluoride 98-56-6	-	11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
Butyl Acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Methyl Amyl Ketone 110-43-0	-	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	-

Aromatic 150 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 41: 96 h Pimephales promelas mg/L LC50	0.95: 48 h Daphnia magna mg/L EC50
Aromatic 100 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4	-	-	5600: 24 h Daphnia magna mg/L EC50
Naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	2.16: 48 h Daphnia magna mg/L LC50 1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Tert-Butyl Acetate 540-88-5	1.38
Parachlorobenzotrifluoride 98-56-6	3.7
Butyl Acetate 123-86-4	1.81
Methyl Amyl Ketone 110-43-0	1.98
Aromatic 150 64742-94-5	2.9 - 6.1
Naphthalene 91-20-3	3.3
Ethyl Benzene 100-41-4	3.118

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001 U055 U165 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145	-	U165
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Butyl Acetate 123-86-4	Toxic
Naphthalene 91-20-3	Toxic
Ethyl Benzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group II
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Description UN1263, Paint, 3, II,
Emergency Response Guide Number 128

TDG

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group II
Description UN1263, Paint, 3, II

MEX

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group II
Description UN1263, Paint, 3, II

ICAO (air)

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

IATA

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
ERG Code	3L
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

IMDG

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
EmS-No.	F-E, S-E
Special Provisions	163
Description	UN1263, Paint, 3, II

RID

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1263, Paint, 3, II

ADR

UN/ID no.	UN1263
Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640D, 650
Description	UN1263, Paint, 3, II, (D/E)
Labels	3

ADN

Proper shipping name	Paint
Hazard Class	3
Packing Group	II
Classification code	F1
Special Provisions	163, 640D, 650
Description	UN1263, Paint, 3, II
Hazard label(s)	3
Limited quantity (LQ)	5 L
Ventilation	VE01

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL/NDL	Complies *
EINECS/ELINCS	Does not comply *

ENCS	Does not comply *
IECSC	Complies *
KECL	Complies *
PICCS	Complies *
AICS	Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Naphthalene	0.1
Ethyl Benzene	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Tert-Butyl Acetate 540-88-5	-	-	-	X
Butyl Acetate 123-86-4	5000 lb	-	-	X
Naphthalene 91-20-3	100 lb	X	X	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tert-Butyl Acetate 540-88-5	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Naphthalene 91-20-3	100 lb 1 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts
Tert-Butyl Acetate 540-88-5	X	X
Parachlorobenzotrifluoride 98-56-6	X	-
Butyl Acetate 123-86-4	X	X
Barium sulfate 7727-43-7	X	X
Methyl Amyl Ketone 110-43-0	X	X
Carbon Black 1333-86-4	X	X
Xylene 1330-20-7	X	X
Naphthalene 91-20-3	X	X
Ethyl Benzene 100-41-4	X	X

Chemical Name	Pennsylvania
Tert-Butyl Acetate 540-88-5	X
Parachlorobenzotrifluoride 98-56-6	X
Butyl Acetate 123-86-4	X
Barium sulfate 7727-43-7	X
Methyl Amyl Ketone 110-43-0	X
Carbon Black 1333-86-4	X

U.S. EPA Label Information**EPA Pesticide Registration Number** Not applicable**Hazardous air pollutants (HAPS) content**

This product contains no reportable Hazardous Air Pollutants

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Revision Date 21-Oct-2016**Revision Note**

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet