

# SAFETY DATA SHEET

Revision Date 21-Oct-2016

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** 8707-BC Hot Fudge

### Other means of identification

**Product Code** DF-8707-BC

**UN/ID no.** UN1263

**SKU(s)** DF-8707-BC

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available.

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Vogel Automotive Coatings

1020 Albany Place SE

Orange City, IA 51041

Phone: 712-737-4993

Fax: 712-737-4997

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Flammable liquids	Category 2

### **Emergency Overview**

#### **Danger**

#### **Hazard statements**

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

Suspected of damaging fertility or the unborn child

Highly flammable liquid and vapor



**Appearance** No information available

**Physical state** liquid

**Odor** No information available

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

- May be harmful if swallowed
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Unknown acute toxicity                      0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Tert-Butyl Acetate	540-88-5	10 - 30	*
Butyl Acetate	123-86-4	5 - 10	*
Parachlorobenzotrifluoride	98-56-6	3 - 7	*
Methyl Amyl Ketone	110-43-0	3 - 7	*
Talc (powder)	14807-96-6	3 - 7	*
Barium sulfate	7727-43-7	1 - 5	*
Acetone	67-64-1	1 - 5	*
Aromatic 150	64742-94-5	1 - 5	*
Aromatic 100	64742-95-6	1 - 5	*
Methyl Isobutyl Ketone	108-10-1	0.1 - 1	*
Carbon Black	1333-86-4	0.1 - 1	*
Stoddard Solvent	8052-41-3	0.1 - 1	*
Toluene	108-88-3	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*
Naphthalene	91-20-3	0.1 - 1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Mineral Spirits	64742-48-9	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician immediately.
<b>Ingestion</b>	Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

Flammable.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Use personal protective equipment as required.

**Environmental precautions**

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong acids. Strong oxidizing agents. Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Tert-Butyl Acetate 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m <sup>3</sup>	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>
Butyl Acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F TWA: 2.5 mg/m <sup>3</sup> dust (vacated) TWA: 2.5 mg/m <sup>3</sup>	-
Methyl Amyl Ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
Talc (powder) 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Barium sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>

Methyl Isobutyl Ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m <sup>3</sup> (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>
Carbon Black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m <sup>3</sup> (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m <sup>3</sup>	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

#### Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Appropriate engineering controls

##### Engineering Controls

Showers  
Eyewash stations  
Ventilation systems.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Tight sealing safety goggles.

##### Skin and body protection

No special technical protective measures are necessary.

##### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

##### Physical state

liquid

##### Appearance

No information available

##### Odor

No information available

##### Color

No information available

##### Odor threshold

No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	>= 56 °C / 133 °F	
Flash point	4 °C / 40 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.13	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

**Other Information**

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	9.45 lbs/gal
Bulk density	No information available
Percent solids by weight	49.7%
Percent volatile by weight	21.0%
Percent solids by volume	33.2%
Actual VOC (lbs/gal)	2
Actual VOC (grams/liter)	237.7
EPA VOC (lbs/gal)	3.3
EPA VOC (grams/liter)	389.6
EPA VOC (lb/gal solids)	6

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong acids. Strong oxidizing agents. Chlorinated compounds.

**Hazardous Decomposition Products**

Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Tert-Butyl Acetate 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h
Butyl Acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg ( Rat ) = 1670 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit ) = 12600 µL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Aromatic 150 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
Aromatic 100 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Methyl Isobutyl Ketone 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
Stoddard Solvent 8052-41-3	-	> 3000 mg/kg (Rabbit)	-
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Naphthalene 91-20-3	= 1110 mg/kg ( Rat ) = 490 mg/kg ( Rat )	(= 1120 mg/kg ( Rabbit ) > 20 g/kg ( Rabbit )	> 340 mg/m <sup>3</sup> ( Rat ) 1 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg ( Rat )	= 0.2 mg/kg ( Rabbit )	= 20 mg/L ( Rat ) 4 h
Mineral Spirits 64742-48-9	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	-

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc (powder) 14807-96-6	-	Group 3	-	-
Methyl Isobutyl Ketone 108-10-1	A3	Group 2B	-	X
Carbon Black 1333-86-4	A3	Group 2B	-	X
Toluene 108-88-3	-	Group 3	-	-
Ethyl Benzene 100-41-4	A3	Group 2B	-	X

Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
------------------------	----	----------	------------------------	---

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity**

**STOT - single exposure**

**STOT - repeated exposure**

**Chronic toxicity**

Product is or contains a chemical which is a known or suspected reproductive hazard.

No information available.

No information available.

Contains a known or suspected reproductive toxin. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands.

**Target Organ Effects**

Central nervous system, Central Vascular System (CVS), Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.

**Aspiration hazard**

No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

44.6% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Tert-Butyl Acetate 540-88-5	-	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	-
Butyl Acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
Parachlorobenzotrifluoride 98-56-6	-	11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
Methyl Amyl Ketone 110-43-0	-	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	-
Talc (powder) 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-
Acetone 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Aromatic 150 64742-94-5	2.5: 72 h Skeletonema costatum mg/L EC50	19: 96 h Pimephales promelas mg/L LC50 static 2.34: 96 h Oncorhynchus mykiss mg/L LC50 1740: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 41: 96 h Pimephales promelas mg/L LC50	0.95: 48 h Daphnia magna mg/L EC50
Aromatic 100 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
Methyl Isobutyl Ketone 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4	-	-	5600: 24 h Daphnia magna mg/L EC50



Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	2.16: 48 h Daphnia magna mg/L LC50 1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodosmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static 320 - 1000: 96 h Leuciscus idus mg/L LC50 static	750: 48 h Daphnia magna mg/L EC50
Mineral Spirits 64742-48-9	-	2200: 96 h Pimephales promelas mg/L LC50	2.6: 96 h Chaetogammarus marinus mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Tert-Butyl Acetate 540-88-5	1.38
Butyl Acetate 123-86-4	1.81
Parachlorobenzotrifluoride 98-56-6	3.7
Methyl Amyl Ketone 110-43-0	1.98
Acetone 67-64-1	-0.24
Aromatic 150 64742-94-5	2.9 - 6.1
Methyl Isobutyl Ketone 108-10-1	1.19
Toluene 108-88-3	2.65
Ethyl Benzene 100-41-4	3.118

Naphthalene 91-20-3	3.3
Methyl Ethyl Ketoxime 96-29-7	0.65

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001 U002 U055 U161 U165 U220 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
Methyl Isobutyl Ketone 108-10-1	-	Included in waste stream: F039	-	U161
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145	-	U165

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

Naphthalene 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-
------------------------	---	---	--	---

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Butyl Acetate 123-86-4	Toxic
Acetone 67-64-1	Ignitable
Toluene 108-88-3	Toxic Ignitable
Ethyl Benzene 100-41-4	Toxic Ignitable
Naphthalene 91-20-3	Toxic

#### 14. TRANSPORT INFORMATION

##### DOT

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28  
 Description UN1263, Paint, 3, II,  
 Emergency Response Guide  
 Number 128

##### TDG

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

##### MEX

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

##### ICAO (air)

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Special Provisions A3, A72

Description UN1263, Paint, 3, II

**IATA**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 ERG Code 3L  
 Special Provisions A3, A72  
 Description UN1263, Paint, 3, II

**IMDG**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 EmS-No. F-E, S-E  
 Special Provisions 163  
 Description UN1263, Paint, 3, II

**RID**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Classification code F1  
 Description UN1263, Paint, 3, II

**ADR**

UN/ID no. UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Classification code F1  
 Tunnel restriction code (D/E)  
 Special Provisions 163, 640D, 650  
 Description UN1263, Paint, 3, II, (D/E)  
 Labels 3

**ADN**

Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Classification code F1  
 Special Provisions 163, 640D, 650  
 Description UN1263, Paint, 3, II  
 Hazard label(s) 3  
 Limited quantity (LQ) 5 L  
 Ventilation VE01

## 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies *
EINECS/ELINCS	Does not comply *
ENCS	Does not comply *
IECSC	Complies *
KECL	Complies *
PICCS	Complies *
AICS	Complies *

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Ethyl Benzene	0.1
Naphthalene	0.1

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Tert-Butyl Acetate 540-88-5	-	-	-	X
Butyl Acetate 123-86-4	5000 lb	-	-	X
Toluene 108-88-3	1000 lb	X	X	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X
Naphthalene 91-20-3	100 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tert-Butyl Acetate 540-88-5	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl Isobutyl Ketone 108-10-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

Naphthalene 91-20-3	100 lb 1 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
------------------------	-------------	---	---

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Methyl Isobutyl Ketone - 108-10-1	Carcinogen Developmental
Carbon Black - 1333-86-4	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
Ethyl Benzene - 100-41-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Cumene - 98-82-8	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts
Tert-Butyl Acetate 540-88-5	X	X
Butyl Acetate 123-86-4	X	X
Parachlorobenzotrifluoride 98-56-6	X	-
Methyl Amyl Ketone 110-43-0	X	X
Talc (powder) 14807-96-6	X	X
Barium sulfate 7727-43-7	X	X
Acetone 67-64-1	X	X
Xylene 1330-20-7	X	X
Methyl Isobutyl Ketone 108-10-1	X	X
Carbon Black 1333-86-4	X	X
Toluene 108-88-3	X	X
Ethyl Benzene 100-41-4	X	X
Naphthalene 91-20-3	X	X

Chemical Name	Pennsylvania
Tert-Butyl Acetate 540-88-5	X
Butyl Acetate 123-86-4	X
Parachlorobenzotrifluoride 98-56-6	X
Methyl Amyl Ketone 110-43-0	X
Talc (powder) 14807-96-6	X
Barium sulfate 7727-43-7	X
Acetone 67-64-1	X

**U.S. EPA Label Information****EPA Pesticide Registration Number** Not applicable

